







Technical Dimensions (mm)




Image




Terminal Dimensions (mm)

Standard Terminal: F1



Optional Terminal: F2



Technical Specification

Output	Nominal Voltage	12V
	Nominal Capacity (20HR)	5Ah
Terminal Type	Standard Terminal	F1
	Optional Terminal	F2
Container Material	Standard Option	ABS
	Flame Retardant Option (FR)	ABS (UL94:VO)
Rated Capacity	(20HR 1.80V/cell, 25°C)	5.0 Ah/0.25A
	(10HR 1.75V/cell, 25°C)	4.7 Ah/0.47A
	(1HR 1.60V/cell, 25°C)	3.25 Ah/3.25A
Max Discharge Current	75A (5s)	
Internal Resistance	Approx 26mΩ	
Discharge Characteristics	Operating Temp Range	Discharge: -15 ~ 50°C
		Charge: 10 ~ 50°C
		Storage: -20 ~ 50°C
	Nominal Operating Temp Range	25 ± 3°C
	Cycle Use	Initial Charging Current less than 1.5A. Voltage 14.5V ~ 14.9V @ 25°C Temp. Coefficient -30mV/°C
	Standby Use	No limit on initial charging current. Voltage 13.6V ~ 13.8V @ 25°C Temp. Coefficient -18mV/°C
Capacity affected by Temperature	40°C	102%
	25°C	100%
	0°C	85%
Design Floating Life at 20°C	5 Years	

Self Discharge


Ultrace//[®] UL batteries may be stored for up to 6 months at 25°C and then a refresh charge is required. For higher temperatures the time intervals will be shorter.

Constant Current Discharge / Constant Power Discharge At 25°C (Amperes & Watts/Cell)


A = Amperes W = Watts

F.V/TIME	5	10	15	30	60	2	3	4	5	10	20
A W min min min min min min hours hours hours hours hours hours											
1.80V/cell	16.0	10.1	8.17	4.73	2.96	1.68	1.21	0.97	0.82	0.46	0.25
	178	114	93.1	54.2	34.3	19.7	14.4	11.6	9.84	5.47	2.94
1.75V/cell	16.9	10.7	8.63	4.91	3.06	1.72	1.25	1.0	0.85	0.47	0.25
	189	120	98.3	56.3	35.4	20.2	14.9	11.9	10.1	5.58	3.0
1.70V/cell	17.7	11.2	8.93	5.04	3.12	1.75	1.26	1.01	0.86	0.47	0.25
	197	126	102	57.7	36.1	20.5	15.0	12.0	10.2	5.61	3.02
1.65V/cell	18.4	11.6	9.27	5.19	3.20	1.77	1.27	1.01	0.86	0.47	0.25
	206	131	106	59.5	37.1	20.7	15.1	12.1	10.3	5.64	3.03
1.60V/cell	19.0	12.0	9.5	5.3	3.25	1.78	1.28	1.02	0.87	0.47	0.25
	212	135	108	60.7	37.6	20.8	15.1	12.1	10.4	1.66	3.05


Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effects of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



General Relation of Capacity vs. Storage Time



General Relation of Capacity vs. Storage Time (Notes)

- A) No supplementary charge required.
(Carryout supplementary charge before use if 100% capacity is required.)
- B) Supplementary charge required before use. Optional charging way as below:
 1. Charged for above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
 2. Charged for above 20 hours at limited current 0.25CA and constant voltage 2.25V/cell.
 3. Charged for 8 ~ 10 hours at limited current 0.05 CA.
- C) Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached.