



OPzV GEL DEEP CYCLE BATTERY

S2-224GEL



Series	GEL	Warranty	See Warranty Terms
Volts	2	BCI	2V OPzV
Cells	1		
Terminal Type	F10		
Included Hardware	Threaded Insert & Bolt		
Size & Thread	F10-M10		

Charge

Recommended Charge Current Capacity (String)	20 A
Maximum Charge Current (String)	60 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)
Internal Resistance	1.02 mΩ

Capacity

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	89%	79%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	301 AH	3.01 A
@ 20 Hour Rate	252 AH	12.6 A
@ 10 Hour Rate	224 AH	22.4 A

Specifications



SAI GLOBAL


ISO 9001
Quality

Weight	18.5 kg	41 lbs
Length	10.3 cm	4.06"
Width	20.6 cm	8.11"
Height Inc. Term.	38.2 cm	15.04"


Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Container	ABS
Cover	ABS
Handles	None

Cycle Life vs. Depth of Discharge



Capacity vs. Temperature



Rev.#3 | May 2018